


The hermetic Wendy luminaire with a high ingress protection IP66 is perfect for rooms such as: warehouses, technical rooms, production halls, garages, underground parking and also corridors. The luminaire body is made of polycarbonate, clamps inox steel. Two types of installation are available: surface mounted and suspended.



IP66

IK08



general data

luminaire body	policarbonate
mounting type	surface mounted / suspended
ingress protection IP	66
operation temperature range	from -20° to +40°
lifetime L80B10	50 000h
impact protection IK	08

electrical data

nominal voltage	220V-240V AC
nominal frequency	50-60Hz
protection class	I
contains light source	yes
connection	connector through
dimming	none (options: DALI)

lighting data


light source	LED
colour rendering index	CRI>80
tolerance of luminous flux	+/-10%

optical data

optical system	shade
material	policarbonate
light emission	direct
light distribution	symmetrical

code	power [W]	luminaire power [W]	luminaire flux [lm]	luminaire efficacy [lm/W]	dimensions [mm]	height [mm]	weight [kg]	box [mm]
E1046.K	20	22	3065	139	1282x101	101	1.8	1300x120x120

K-colour temperature



accessories

- E01 set of mechanical suspensions 1000mm (2 pcs)
- E02 set of mechanical suspensions 4000mm (2 pcs)
- E09 canopy with power supply, white, square, with a transparent cable, length 1000mm